





*Attention: Read and understand these instructions before installing fixture. This fixture is intended for installation in accordance with National Electric Code and local regulation: To assure full compliance with local codes and regulations, check with your local electrical inspector before installation. This equipment is guaranteed only when used as indicated in these instructions; therefore they should be kept for future reference. To prevent electrical shock, turn off power supply before carrying out any connection or maintenance operations.*

Make sure you have all the elements to complete the installation. Depending on configuration selected, you must have the following:

Driver Housing	<p>Surface model</p>	<p>Recessed model</p>
Grafa Fixture	<p>Rectangle model</p>	<p>Square model</p>
Mounting Clip/ Cable Kit		

## STEP 1


3.1 Install the Driver Housing, following the Instruction sheet supplied with it (document Y503-11401).





**STEP 2**




Mark the location of the suspension cables on the ceiling using the measurements specific to your configuration.



**STEP 3**



Install the cable couplers to the ceiling to the marked locations using the proper hardware (not supplied)

4x



**STEP 4**

4.1 Install the brackets to the fixture.







**STEP 5**

5.1 Loosen the gripper tip to allow insertion and insert the suspension cable through the gripper.  
5.2 Feed the suspension cables into the coupler, then screw the gripper in. Repeat steps for all cables.

5.1




5.2




**STEP 6**

6.1 Loosen the bottom of the cable gripper in order to adjust fixture height. Pressing on it unlocks cable movement.  
6.2 Once fixture is level enough, tighten bottom of the cable gripper in order to lock it into position.

6.1





6.2





**STEP 6 (cont.)**


6.3 Rotate the micro adjustment wheel on the bottom of the suspension cable to get a perfectly leveled fixture.




**STEP 7**

7.1 On the fixture, lift up the terminal cover to expose the wiring connections.  
7.2 Remove the screws holding the strain relief bracket.

7.1



7.2







**STEP 7 (cont.)**

7.3 Route the power cable into the fixture and connect it to the location labeled "A".

7.4 Screw the strain relief bracket back in, securing the power cable in place. Snap the terminal cover back on. The fixture installation is now complete.



7.3



7.4

