


# GRAFA STANDALONE

Design Wilmotte & Industries

#CAT	family	shape	housing	cord length	CRI	CCT	driver	body color	bracket color
USC-M	GRK	—	—	6	8	—	08	A	—

Quantity

family	<b>GRK</b> = Grafa Standalone
shape	<b>R</b> = Rectangle (1200x300mm) <b>S</b> = Square (600x600mm)
housing	<b>R</b> = Recessed <b>S</b> = Surface
cord length	<b>6</b> = 6 feet
CRI	<b>8</b> = 85CRI TYP
CCT	<b>30</b> = 3000K <b>35</b> = 3500K
driver	<b>08</b> = On/Off + 0-10V UNV
body color	<b>A</b> = Clear Anodized
bracket color	<b>0</b> = Grey <b>1</b> = Anthracite <b>2</b> = White <b>3</b> = Blue <b>4</b> = Red <b>5</b> = Green



## SPECIFICATIONS:

Power input : 48W  
Luminous flux : 4123lm (estimated)  
Efficacy: 86lm/W (estimated)

## FEATURES:

Standalone module with direct and indirect emission, with high LED efficiency.  
Installation with suspension.

**Construction** : structure in extruded aluminum, anodized clear matte, top screen with anti-dust polycarbonate and staple brackets in 6 different powder coat colors. Suspension cables in steel with quick adjustment.

**Notes** : For all other finishes, please contact your local Artemide sales representative.

**Weight** : 9lbs (4Kg), both versions


**Label** : - suitable for dry locations

**Class** : IP20

## PHOTOMETRIC DATA:

Photometric curve :

3500K



cd/klm

H m	Ø m	EMax lux	EM lux
1	1.90	1078	430
2	3.80	270	108
3	5.71	120	48
4	7.61	68	27
5	9.51	44	18