

## LINEAFLAT wall/ceiling


design Artemide North America



#CAT	LENGTH	EMISSION	CRI	CCT	DRIVER	FINISH
<b>USC-RDLF</b>						

QUANTITY

Length	<b>M</b> = mini <b>1</b> = 12in <b>2</b> = 24in <b>3</b> = 36in
Emission	<b>D</b> = mono (1 side illuminated) <b>B</b> = dual (2 side illuminated)
CRI	<b>8</b> = 80 CRI+ <b>9</b> = 90 CRI+
CCT	<b>30</b> = 3000k <b>35</b> = 3500k
Driver	<b>06</b> = Phase Dimming 2-wire 120V* (also on/off 277V) <b>08</b> = 0-10V Dimming 120V-277V
Finish	<b>AN</b> = textured Anthracite powder coat <b>W</b> = textured White powder coat



\*Compatible with most forward or reverse phase dimmers.

### TECHNICAL DATA : (80CRI 3500K model rating)

	mini	1	2	3
<b>Dual</b>				
Input Powder	12.2 W	19.6 W	41.8 W	58.8 W
Lumen Output	516 lm	874 lm	1835 lm	2560 lm
Efficacy	42.4 lm/W	44.6 lm/W	43.8 lm/W	43.5 lm/W
<b>Mono</b>				
Input Powder	6.1 W	9.8 W	20.9 W	29.4 W
Lumen Output	258 lm	437 lm	917 lm	1280 lm
Efficacy	42.4 lm/W	44.6 lm/W	43.8 lm/W	43.5 lm/W

### FEATURES:

**Construction** : Body in extruded aluminum with textured powder coat finish. End caps in aluminum same color as the body. Extrusion covers junction box dimension. 'Pig-tail' option on backplate available on 1, 2 and 3 feet only.

**Note** : For other finishes, please contact your local Artemide sales representative.

### Weight

**mini** - 2lbs (0.9kg)

**1** - 3lbs (1.3kg)


**2** - 6lbs (2.7kg)

**3** - 8lbs (3.6kg)


Labels : cULus - suitable for damp locations ADA

Class : IP20


### PHOTOMETRIC DATA:




Max Candela linea mini  
130° vertical = 178  
180° horizontal = 178



Max Candela linea 1ft  
132.5° vertical = 306  
180° horizontal = 306



Max Candela linea 2ft  
135° vertical = 638  
180° horizontal = 638



Max Candela linea 3ft  
132.5° vertical = 865  
180° horizontal = 865