




Attention: Read and understand these instructions before installing fixture. This fixture is intended for installation in accordance with National Electric Code and local regulation: To assure full compliance with local codes and regulations, check with your local electrical inspector before installation. This equipment is guaranteed only when used as indicated in these instructions; therefore they should be kept for future reference. To prevent electrical shock, turn off power supply before carrying out any connection or maintenance operations.


NOTE 1

The electrical feed is rated at 6A maximum, make sure the sum of gear plates on the same circuit does not exceed it. Consult the gear plate datasheets to find the values.




STEP 1

Make sure your box has the following parts:



NOTE 2

The Electrical feed position must be verified as it can interfere with the body's mounting brackets.








STEP 2

Choose your installation type

Armored Cable ("BX" pigtail)





connection housing




the canopy cover will not be used. It is represented graphically in some steps, disregard as installation process is the same.


Insert the armored cable through the connection housing and secure into place with the nut. Using the appropriate hardware (not supplied), mount the housing to the surface.





Electrical Junction Box



Install the mandatory canopy cover using the 2 philips screws.



Insert the junction box wiring through the canopy cover hole. Using the appropriate hardware (not supplied), mount the housing to the surface.






STEP 3


Choose how the power will be fed to the gear plate and proceed with the following steps

If feeding from the edge of the fixture, use the small wire bundle that comes with the gear plate. Continue to Step 3.




the feed cable will not be used.

If feeding from the center of the fixture, use the feed cable supplied in the kit.




Pry out the knock-out opening, insert the protective grommet and insert feed cable through grommet.



STEP 4

Make the appropriate connections going to the fixture depending on your installation type.



To Fixture


CEILING WIRES		HOUSING WIRES
GREEN	G	GREEN/YELLOW
BLACK	L	BLACK
WHITE	N	WHITE

0-10V DIMMABLE VERSION:

CEILING WIRES		HOUSING WIRES
0-10V (+)	+	VIOLET (+)
0-10V (-)	-	GREY (-)

DALI DIMMABLE VERSION:

CEILING WIRES		HOUSING WIRES
DALI	DA	VIOLET
DALI	DA	GREY



To Fixture



STEP 4

Continue with Body, Gear Plate and Optics installation using each component's respective Installation Document.

