

Luminaire

Code M2883W01+M196900

Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 3000K DIMMERABILE 1184MM + INDIRETTA LED+ OTTICA PRISMOPTIC PER LED


Measurement

Code FTS1601405

Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 3000K DIMMERABILE 1184MM + INDIRETTA LED+ OTTICA PRISMOPTIC PER LED

Luminaire Flux	5002.52 lm	Luminaire Power	62.00 W	Efficacy	80.69 lm/W	Efficiency	100.00%
Lamps Flux	5002.52 lm	Maximum value	237.61 cd/klm	Position	C=90.00 G=1.00	CG Asymmetrical	
Rectangular Luminaire		Length	1185 mm	Width	45 mm	Height	110 mm
Rectangular Luminous Area		Length	1185 mm	Width	32 mm	Height	0 mm
Horizontal Luminous Area		0.037920 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.009174 m2	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		24-06-2016		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5002.52 lm	
LED Flux=7571,94lm LED Power=48W Eff=66% EfcLed=158lm/W EfcLum=81lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	57 86 97 50 100			D DIN 5040	C41		
F UTE	0.50 D + 0.50 T			B NBN	BZ 3		

1185mm x 45mm




Semipiani C

180.0 ——— 0.0
270.0 - - - - 90.0

ULOR 49.77 %

DLOR 50.23 %

RN 49.77 %



Luminaire

Code M2883W01+M196900

Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 3000K DIMMERABILE 1184MM + INDIRETTA LED+ OTTICA PRISMOPTIC PER LED

Measurerm.

Code FTS1601405


Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 3000K DIMMERABILE 1184MM + INDIRETTA LED+ OTTICA PRISMOPTIC PER LED

Luminaire Flux	5002.52 lm	Luminaire Power	62.00 W	Efficacy	80.69 lm/W	Efficiency	100.00%
Lamps Flux	5002.52 lm	Maximum value	237.61 cd/klm	Position	C=90.00 G=1.00	CG Asymmetrical	
Rectangular Luminaire		Length	1185 mm	Width	45 mm	Height	110 mm
Rectangular Luminous Area		Length	1185 mm	Width	32 mm	Height	0 mm
Horizontal Luminous Area		0.037920 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.009174 m2	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		24-06-2016		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5002.52 lm	
LED Flux=7571,94lm LED Power=48W Eff=66% EfcLed=158lm/W EfcLum=81lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	57 86 97 50 100			D DIN 5040	C41		
F UTE	0.50 D + 0.50 T			B NBN	BZ 3		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.81	1.63	2.44	3.25	4.07	OC	1.23	2.46	3.69	4.93	6.16
OB	0.81	1.63	2.44	3.25	4.07	OD	1.23	2.46	3.69	4.93	6.16

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1187.88	1181.44	1101.30	922.23	687.10	475.42	297.03	173.05	86.91	24.46
OB	1187.88	1181.44	1101.30	922.23	687.10	475.42	297.03	173.05	86.91	24.46
OC	1187.88	1182.67	1132.70	1034.38	893.21	714.26	505.23	286.44	121.65	27.42
OD	1187.88	1182.67	1132.70	1034.38	893.21	714.26	505.23	286.44	121.65	27.42



H[m]	D[m]	Max lux	Med lux	Alpha=39.1°+39.1°	G=0.0
1.00	1.63	1188	425		
2.00	3.25	297	106		
3.00	4.88	132	47		
4.00	6.51	74	27		
5.00	8.13	48	17		

H[m]	D[m]	Max lux	Med lux	Beta=50.9°+50.9°	G=0.0
1.00	2.46	1188	425		
2.00	4.93	297	106		
3.00	7.39	132	47		
4.00	9.85	74	27		
5.00	12.31	48	17		

Luminaire

Code M2883W01+M196900

Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 3000K DIMMERABILE 1184MM + INDIRETTA LED+ OTTICA PRISMOPTIC PER LED

Measur.

Code FTS1601405

Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 3000K DIMMERABILE 1184MM + INDIRETTA LED+ OTTICA PRISMOPTIC PER LED

Luminaire Flux	5002.52 lm	Luminaire Power	62.00 W	Efficacy	80.69 lm/W	Efficiency	100.00%
Lamps Flux	5002.52 lm	Maximum value	237.61 cd/klm	Position	C=90.00 G=1.00	CG Asymmetrical	

UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	17.3	18.1	18.2	18.9	22.5	19.7	20.5	20.6	21.3	22.5
x=2H y=3H	18.2	18.8	19.1	19.7	23.4	20.7	21.4	21.6	22.3	23.4
x=2H y=4H	18.5	19.1	19.4	20.1	23.8	21.0	21.7	22.0	22.6	23.8
x=2H y=6H	18.8	19.4	19.7	20.3	23.9	21.2	21.8	22.2	22.7	23.9
x=2H y=8H	18.9	19.4	19.8	20.3	23.9	21.3	21.8	22.2	22.7	23.9
x=2H y=12H	18.9	19.4	19.9	20.4	23.9	21.3	21.8	22.2	22.7	23.9
x=4H y=2H	17.9	18.5	18.8	19.4	22.5	19.8	20.4	20.7	21.3	22.5
x=4H y=3H	18.9	19.4	19.8	20.3	23.6	21.0	21.5	21.9	22.4	23.6
x=4H y=4H	19.3	19.8	20.3	20.7	24.0	21.4	21.8	22.4	22.8	24.0
x=4H y=6H	19.7	20.1	20.6	21.0	24.3	21.7	22.1	22.7	23.0	24.3
x=4H y=8H	19.8	20.1	20.8	21.1	24.4	21.8	22.1	22.8	23.1	24.4
x=4H y=12H	19.9	20.2	20.9	21.2	24.4	21.8	22.1	22.8	23.1	24.4
x=8H y=4H	19.5	19.9	20.5	20.8	24.0	21.4	21.8	22.4	22.7	24.0
x=8H y=6H	20.0	20.3	21.0	21.3	24.4	21.8	22.1	22.8	23.1	24.4
x=8H y=8H	20.2	20.4	21.2	21.4	24.5	21.9	22.2	22.9	23.2	24.5
x=8H y=12H	20.3	20.5	21.3	21.5	24.6	22.0	22.2	23.0	23.3	24.6
x=12H y=4H	19.5	19.8	20.5	20.8	24.0	21.3	21.7	22.4	22.7	24.0
x=12H y=6H	20.0	20.2	21.0	21.3	24.3	21.8	22.0	22.8	23.0	24.3
x=12H y=8H	20.2	20.4	21.3	21.5	24.5	21.9	22.1	23.0	23.2	24.5