

Luminaire


Code AE30000+AE43001
Name A. SHARPING 2368.DIR.6X4 930 DM FLOOD + SCREENS 2368 6X4 WHITE

Measurem.

Code FTS1603116
Name A. SHARPING 2368.DIR.6X4 930 DM FLOOD + SCREENS 2368 6X4 WHITE

Luminaire Flux	4641.36 lm	Luminaire Power	72.00 W	Efficacy	64.46 lm/W	Efficiency	100.00%
Lamps Flux	4641.36 lm	Maximum value	5541.55 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.032856 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007949 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4641.36 lm	
LED Flux=6128lm LED Power=63W Eff=76% EfcLed=97lm/W EfcLum=64lm/W Ra=90 SDCM=2 L90(6K)=50000h							
C.I.E.	99	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	

2368mm x 40mm




Semipiani C

180.0 — 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code AE30000+AE43001
Name A. SHARPING 2368.DIR.6X4 930 DM FLOOD + SCREENS 2368 6X4 WHITE

Measur.


Code FTS1603116
Name A. SHARPING 2368.DIR.6X4 930 DM FLOOD + SCREENS 2368 6X4 WHITE

Luminaire Flux	4641.36 lm	Luminaire Power	72.00 W	Efficacy	64.46 lm/W	Efficiency	100.00%
Lamps Flux	4641.36 lm	Maximum value	5541.55 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.032856 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007949 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4641.36 lm	
LED Flux=6128lm LED Power=63W Eff=76% EfcLed=97lm/W EfcLum=64lm/W Ra=90 SDCM=2 L90(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.35	0.53	0.70	0.88	OC	0.18	0.35	0.53	0.70	0.88
OB	0.18	0.35	0.53	0.70	0.88	OD	0.18	0.35	0.53	0.70	0.88

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	25720.34	21888.11	6752.74	1846.32	115.85	32.68	11.36	7.28	5.16	2.43
OB	25720.34	21888.11	6752.74	1846.32	115.85	32.68	11.36	7.28	5.16	2.43
OC	25720.34	21888.11	6752.74	1846.32	115.85	32.68	11.36	7.28	5.16	2.43
OD	25720.34	21888.11	6752.74	1846.32	115.85	32.68	11.36	7.28	5.16	2.43



H[m]	D[m]	Max lux	Med lux	Alpha=10.0°+10.0°	G=0.0
1.00	0.35	25720	16400		
2.00	0.70	6430	4100		
3.00	1.05	2858	1822		
4.00	1.41	1608	1025		
5.00	1.76	1029	656		

Luminaire

Code AE30000+AE43001

Name A. SHARPING 2368.DIR.6X4 930 DM FLOOD + SCREENS 2368 6X4 WHITE

Measurem.

Code FTS1603116

Name A. SHARPING 2368.DIR.6X4 930 DM FLOOD + SCREENS 2368 6X4 WHITE

Luminaire Flux	4641.36 lm	Luminaire Power	72.00 W	Efficacy	64.46 lm/W	Efficiency	100.00%
Lamps Flux	4641.36 lm	Maximum value	5541.55 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions										
RoomDimensions	ViewedCrosswise					ViewedEndwise				
	1.4	2.0	1.7	2.2	2.4	1.4	2.0	1.7	2.2	2.4
x=2H y=2H	1.4	2.0	1.7	2.2	2.4	1.4	2.0	1.7	2.2	2.4
x=2H y=3H	1.7	2.3	2.0	2.6	2.8	1.7	2.3	2.0	2.6	2.8
x=2H y=4H	2.0	2.6	2.3	2.8	3.1	2.0	2.6	2.3	2.8	3.1
x=2H y=6H	2.3	2.8	2.7	3.1	3.4	2.3	2.8	2.7	3.1	3.4
x=2H y=8H	2.5	3.0	2.8	3.3	3.6	2.5	3.0	2.8	3.3	3.6
x=2H y=12H	2.7	3.1	3.0	3.4	3.7	2.7	3.1	3.0	3.4	3.7
x=4H y=2H	1.4	2.0	1.7	2.2	2.5	1.4	2.0	1.7	2.2	2.5
x=4H y=3H	1.9	2.4	2.3	2.7	3.0	1.9	2.4	2.3	2.7	3.0
x=4H y=4H	2.4	2.8	2.8	3.1	3.4	2.4	2.8	2.8	3.1	3.4
x=4H y=6H	2.9	3.2	3.3	3.6	4.0	2.9	3.2	3.3	3.6	4.0
x=4H y=8H	3.2	3.5	3.6	3.8	4.2	3.2	3.5	3.6	3.8	4.2
x=4H y=12H	3.4	3.7	3.9	4.1	4.5	3.4	3.7	3.9	4.1	4.5
x=8H y=4H	2.6	2.9	3.0	3.2	3.6	2.6	2.9	3.0	3.2	3.6
x=8H y=6H	3.2	3.5	3.7	3.9	4.3	3.2	3.5	3.7	3.9	4.3
x=8H y=8H	3.6	3.8	4.1	4.3	4.7	3.6	3.8	4.1	4.3	4.7
x=8H y=12H	4.0	4.2	4.5	4.6	5.1	4.0	4.2	4.5	4.6	5.1
x=12H y=4H	2.6	2.8	3.0	3.2	3.6	2.6	2.8	3.0	3.2	3.6
x=12H y=6H	3.3	3.5	3.8	3.9	4.4	3.3	3.5	3.8	3.9	4.4
x=12H y=8H	3.8	3.9	4.2	4.4	4.9	3.8	3.9	4.2	4.4	4.9