

Luminaire

Code AA00001_DMX_W
Name LOT RIFR.PROJ.LED R+W BCO - DMX CH1 0- CH2 0- CH3 0- CH4 0- CH5 0- CH6 255

Measurement

Code FTS1700326
Name LOT RIFR.PROJ.LED R+W BCO - DMX CH1 0- CH2 0- CH3 0- CH4 0- CH5 0- CH6 255

Luminaire Flux	266.88 lm	Luminaire Power	60.00 W	Efficacy	4.45 lm/W	Efficiency	100.00%
Lamps Flux	266.88 lm	Maximum value	360.84 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area		Length Diam.	180 mm 180 mm	Width Height	1 mm 0 mm	Height	80 mm
Horizontal Luminous Area		0.025447 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.006156 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-03-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		266.88 lm	
Continuous Power=60 Peak Power=85W WHITE L70(6K)=50000 h							
C.I.E.	52 84 97 100 100			D DIN 5040		A40	
F UTE	1.00 D			B NBN		BZ 4	

180mm x 1mm




Semipiani C

180.0 — 0.0

ULOR 0.01 %

DLOR 99.99 %

RN 0.01 %



Luminaire

Code AA00001_DMX_W
Name LOT RIFR.PROJ.LED R+W BCO - DMX CH1 0- CH2 0- CH3 0- CH4 0- CH5 0- CH6 255

Measurerm.


Code FTS1700326
Name LOT RIFR.PROJ.LED R+W BCO - DMX CH1 0- CH2 0- CH3 0- CH4 0- CH5 0- CH6 255

Luminaire Flux	266.88 lm	Luminaire Power	60.00 W	Efficacy	4.45 lm/W	Efficiency	100.00%
Lamps Flux	266.88 lm	Maximum value	360.84 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area		Length Diam.	180 mm 180 mm	Width Height	1 mm 0 mm	Height	80 mm
Horizontal Luminous Area		0.025447 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.006156 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-03-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		266.88 lm	
Continuous Power=60 Peak Power=85W WHITE L70(6K)=50000 h							
C.I.E.	52 84 97 100 100			D DIN 5040	A40		
F UTE	1.00 D			B NBN	BZ 4		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.34	2.68	4.01	5.35	6.69	OC	1.34	2.68	4.01	5.35	6.69
OB	1.34	2.68	4.01	5.35	6.69	OD	1.34	2.68	4.01	5.35	6.69

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	96.30	96.08	91.28	82.14	91.89	71.46	44.45	25.98	12.18	2.19
OB	96.30	96.08	91.28	82.14	91.89	71.46	44.45	25.98	12.18	2.19
OC	96.30	96.08	91.28	82.14	91.89	71.46	44.45	25.98	12.18	2.19
OD	96.30	96.08	91.28	82.14	91.89	71.46	44.45	25.98	12.18	2.19



H[m]	D[m]	Max lux	Med lux	Alpha=53.2°+53.2°	G=0.0
1.00	2.68	96	29		
2.00	5.35	24	7		
3.00	8.03	11	3		
4.00	10.71	6	2		
5.00	13.38	4	1		