

Luminaire

Code AF10201+AF95204

Name SHARP RECESSED TRIM 4X 12W 927 VERY WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK


Measurem.

Code FTS1603148

Name SHARP RECESSED TRIM 4X 12W 927 VERY WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Luminaire Flux	713.68 lm	Luminaire Power	11.00 W	Efficacy	64.88 lm/W	Efficiency	100.00%
Lamps Flux	713.68 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	150 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	148 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.005476 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001325 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		713.68 lm	
LED Flux=996,2lm LED Power=11W Eff=72% EfcLed=91lm/W EfcLum=65lm/W Ra=90 SDCM=2 L90(6K)=50000h							
C.I.E.	99	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	

150mm x 40mm




Semipiani C

180.0 — 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code AF10201+AF95204

Name SHARP RECESSED TRIM 4X 12W 927 VERY WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Measur.

Code FTS1603148


Name SHARP RECESSED TRIM 4X 12W 927 VERY WIDE FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Luminaire Flux	713.68 lm	Luminaire Power	11.00 W	Efficacy	64.88 lm/W	Efficiency	100.00%
Lamps Flux	713.68 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	150 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	148 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.005476 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001325 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		713.68 lm	
LED Flux=996,2lm LED Power=11W Eff=72% EfcLed=91lm/W EfcLum=65lm/W Ra=90 SDCM=2 L90(6K)=50000h							
C.I.E.	99	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.49	0.98	1.47	1.96	2.44	OC	0.49	0.98	1.47	1.96	2.44
OB	0.49	0.98	1.47	1.96	2.44	OD	0.49	0.98	1.47	1.96	2.44

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1021.25	1013.91	925.77	615.79	109.03	15.90	1.24	0.00	0.00	0.00
OB	1021.25	1013.91	925.77	615.79	109.03	15.90	1.24	0.00	0.00	0.00
OC	1021.25	1013.91	925.77	615.79	109.03	15.90	1.24	0.00	0.00	0.00
OD	1021.25	1013.91	925.77	615.79	109.03	15.90	1.24	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=26.1°+26.1°	G=0.0
1.00	0.98	1021	616		
2.00	1.96	255	154		
3.00	2.93	113	68		
4.00	3.91	64	39		
5.00	4.89	41	25		