

Luminaire


Code AF20001+AF95204
Name SHARP RECESSED TRIM 12X 36W 930 FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Measur.

Code FTS1603161
Name SHARP RECESSED TRIM 12X 36W 930 FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Luminaire Flux	2227.39 lm	Luminaire Power	33.00 W	Efficacy	67.50 lm/W	Efficiency	100.00%
Lamps Flux	2227.39 lm	Maximum value	5604.42 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	464 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	444 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.016428 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.003974 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2227.39 lm	
LED Flux=2988,6lm LED Power=33W Eff=75% EfcLed=91lm/W EfcLum=67lm/W Ra=90 SDCM=2 L90(6K)=50000h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1


464mm x 40mm



Semipiani C

180.0 — 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire

Code AF20001+AF95204

Name SHARP RECESSED TRIM 12X 36W 930 FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Measurem.

Code FTS1603161


Name SHARP RECESSED TRIM 12X 36W 930 FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Luminaire Flux	2227.39 lm	Luminaire Power	33.00 W	Efficacy	67.50 lm/W	Efficiency	100.00%
Lamps Flux	2227.39 lm	Maximum value	5604.42 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	464 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	444 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.016428 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.003974 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2227.39 lm	
LED Flux=2988,6lm LED Power=33W Eff=75% EfcLed=91lm/W EfcLum=67lm/W Ra=90 SDCM=2 L90(6K)=50000h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.35	0.53	0.70	0.88	OC	0.18	0.35	0.53	0.70	0.88
OB	0.18	0.35	0.53	0.70	0.88	OD	0.18	0.35	0.53	0.70	0.88

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	12483.24	10614.95	3259.12	871.81	51.62	10.92	1.37	0.00	0.00	0.00
OB	12483.24	10614.95	3259.12	871.81	51.62	10.92	1.37	0.00	0.00	0.00
OC	12483.24	10614.95	3259.12	871.81	51.62	10.92	1.37	0.00	0.00	0.00
OD	12483.24	10614.95	3259.12	871.81	51.62	10.92	1.37	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=10.0°+10.0°	G=0.0
1.00	0.35	12483	7965		
2.00	0.70	3121	1991		
3.00	1.05	1387	885		
4.00	1.40	780	498		
5.00	1.75	499	319		

Luminaire

Code AF20001+AF95204

Name SHARP RECESSED TRIM 12X 36W 930 FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Measurem.

Code FTS1603161

Name SHARP RECESSED TRIM 12X 36W 930 FLOOD WHITE EXT.DRV + SCREEN 4X BLACK

Luminaire Flux	2227.39 lm	Luminaire Power	33.00 W	Efficacy	67.50 lm/W	Efficiency	100.00%
Lamps Flux	2227.39 lm	Maximum value	5604.42 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	< 0	0.6	0.2	0.8	1.0	< 0	0.6	0.2	0.8	1.0
x=2H y=3H	< 0	0.5	0.2	0.7	0.9	< 0	0.5	0.2	0.7	0.9
x=2H y=4H	< 0	0.3	0.1	0.6	0.8	< 0	0.3	0.1	0.6	0.8
x=2H y=6H	< 0	0.2	0.0	0.5	0.8	< 0	0.2	0.0	0.5	0.8
x=2H y=8H	< 0	0.2	0.0	0.4	0.7	< 0	0.2	0.0	0.4	0.7
x=2H y=12H	< 0	0.1	< 0	0.4	0.7	< 0	0.1	< 0	0.4	0.7
x=4H y=2H	< 0	0.3	0.1	0.6	0.8	< 0	0.3	0.1	0.6	0.8
x=4H y=3H	< 0	0.1	< 0	0.4	0.7	< 0	0.1	< 0	0.4	0.7
x=4H y=4H	< 0	< 0	< 0	0.3	0.6	< 0	< 0	< 0	0.3	0.6
x=4H y=6H	< 0	< 0	< 0	0.2	0.6	< 0	< 0	< 0	0.2	0.6
x=4H y=8H	< 0	< 0	< 0	0.1	0.5	< 0	< 0	< 0	0.1	0.5
x=4H y=12H	< 0	< 0	< 0	0.1	0.5	< 0	< 0	< 0	0.1	0.5
x=8H y=4H	< 0	< 0	< 0	0.1	0.5	< 0	< 0	< 0	0.1	0.5
x=8H y=6H	< 0	< 0	< 0	0.0	0.4	< 0	< 0	< 0	0.0	0.4
x=8H y=8H	< 0	< 0	< 0	< 0	0.4	< 0	< 0	< 0	< 0	0.4
x=8H y=12H	< 0	< 0	< 0	< 0	0.4	< 0	< 0	< 0	< 0	0.4
x=12H y=4H	< 0	< 0	< 0	0.1	0.5	< 0	< 0	< 0	0.1	0.5
x=12H y=6H	< 0	< 0	< 0	< 0	0.4	< 0	< 0	< 0	< 0	0.4
x=12H y=8H	< 0	< 0	< 0	< 0	0.4	< 0	< 0	< 0	< 0	0.4