


Luminaire

Code 2124C10A
Name AoL SYSTEM S CURVA UP 3500K


Measurem.

Code FTS1902632
Name AoL SYSTEM S CURVA UP 3500K

Luminaire Flux	645.43 lm	Luminaire Power	8.00 W	Efficacy	80.68 lm/W	Efficiency	100.00%
Lamps Flux	645.43 lm	Maximum value	151.82 cd/klm	Position	C=0.00 G=48.00	CG	Sym. on planes 0-180
Rectangular Luminaire		Length	50 mm	Width	50 mm	Height	580 mm
Rectangular Luminous Area		Length	50 mm	Width	50 mm	Height	580 mm
Horizontal Luminous Area		0.002500 m2		Emitting area on Plane 180°		0.029000 m2	
Emitting area on Plane 0°		0.029000 m2		Emitting area on Plane 270°		0.029000 m2	
Emitting area on Plane 90°		0.029000 m2		Glare area at 76°		0.028743 m2	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		13-09-2019		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		645.43 lm	
LED Flux=917lm LED Power=8W Eff=70% EfcLed=115lm/W EfcLum=81lm/W CCT=3500K Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	26 52 77 64 100			D DIN 5040	B11		
F UTE	0.64 J + 0.36 T			B NBN	BZ 8		



ULOR 35.91 %
DLOR 64.09 %
RN 35.91 %



Luminaire

Code 2124C10A
Name AoL SYSTEM S CURVA UP 3500K

Measur.

Code FTS1902632
Name AoL SYSTEM S CURVA UP 3500K

Luminaire Flux	645.43 lm	Luminaire Power	8.00 W	Efficacy	80.68 lm/W	Efficiency	100.00%
Lamps Flux	645.43 lm	Maximum value	151.82 cd/klm	Position	C=0.00 G=48.00	CG	Sym. on planes 0-180
Rectangular Luminaire		Length	50 mm	Width	50 mm	Height	580 mm
Rectangular Luminous Area		Length	50 mm	Width	50 mm	Height	580 mm
Horizontal Luminous Area		0.002500 m2		Emitting area on Plane 180°		0.029000 m2	
Emitting area on Plane 0°		0.029000 m2		Emitting area on Plane 270°		0.029000 m2	
Emitting area on Plane 90°		0.029000 m2		Glare area at 76°		0.028743 m2	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		13-09-2019		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		645.43 lm	
LED Flux=917lm LED Power=8W Eff=70% EfcLed=115lm/W EfcLum=81lm/W CCT=3500K Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	26 52 77 64 100			D DIN 5040	B11		
F UTE	0.64 J + 0.36 T			B NBN	BZ 8		

Apertura a destra non trovata, gamma =48

Apertura a destra non trovata, gamma =48

Apertura a destra non trovata, gamma =48