

Luminaire


Code 1212ae00A
Name Alphabet of light - æ + support

Measurem.

Code FTS1700541
Name Alphabet of light - æ + support

Luminaire Flux	2016.00 lm	Luminaire Power	32.00 W	Efficacy	63.00 lm/W	Efficiency	100.00%
Lamps Flux	2016.00 lm	Maximum value	138.19 cd/klm	Position	C=180.00 G=90.00	CG Sym. on planes 0-180	
Rectangular Luminaire		Length	960 mm	Width	50 mm	Height	660 mm
Rectangular Luminous Area		Length	960 mm	Width	50 mm	Height	660 mm
Horizontal Luminous Area		0.048000 m2		Emitting area on Plane 180°		0.633600 m2	
Emitting area on Plane 0°		0.633600 m2		Emitting area on Plane 270°		0.033000 m2	
Emitting area on Plane 90°		0.033000 m2		Glare area at 76°		0.626392 m2	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		05-04-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2016.00 lm	
LED Flux=2912,12lm LED Power=32W Eff=69% EfcLed=91lm/W EfcLum=63lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	21 46 73 50 100			D DIN 5040	C11		
F UTE	0.50 J + 0.50 T			B NBN	BZ 9		

960mm x 50mm




Semipiani C

180.0 ——— 0.0
270.0 - - - - - 90.0

ULOR 50.00 %

DLOR 50.00 %

RN 50.00 %



Luminaire

Code 1212ae00A
Name Alphabet of light - æ + support

Measur.

Code FTS1700541
Name Alphabet of light - æ + support

Luminaire Flux	2016.00 lm	Luminaire Power	32.00 W	Efficacy	63.00 lm/W	Efficiency	100.00%
Lamps Flux	2016.00 lm	Maximum value	138.19 cd/klm	Position	C=180.00 G=90.00	CG Sym. on planes 0-180	
Rectangular Luminaire		Length	960 mm	Width	50 mm	Height	660 mm
Rectangular Luminous Area		Length	960 mm	Width	50 mm	Height	660 mm
Horizontal Luminous Area		0.048000 m2		Emitting area on Plane 180°		0.633600 m2	
Emitting area on Plane 0°		0.633600 m2		Emitting area on Plane 270°		0.033000 m2	
Emitting area on Plane 90°		0.033000 m2		Glare area at 76°		0.626392 m2	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		05-04-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2016.00 lm	
LED Flux=2912,12lm LED Power=32W Eff=69% EfcLed=91lm/W EfcLum=63lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	21 46 73 50 100			D DIN 5040	C11		
F UTE	0.50 J + 0.50 T			B NBN	BZ 9		

Apertura a sinistra non trovata, gamma =-90

Apertura a sinistra non trovata, gamma =-90

Apertura a sinistra non trovata, gamma =-90