

## Luminaire


Code 1212t00A  
Name Alphabet of light - t + support

## Measurem.

Code FTS1700498  
Name Alphabet of light - t + support

Luminaire Flux	1006.00 lm	Luminaire Power	17.00 W	Efficacy	59.18 lm/W	Efficiency	100.00%
Lamps Flux	1006.00 lm	Maximum value	138.19 cd/klm	Position	C=180.00 G=90.00	CG Sym. on planes 0-180	
Rectangular Luminaire		Length	360 mm	Width	50 mm	Height	960 mm
Rectangular Luminous Area		Length	360 mm	Width	50 mm	Height	960 mm
Horizontal Luminous Area		0.018000 m2		Emitting area on Plane 180°		0.345600 m2	
Emitting area on Plane 0°		0.345600 m2		Emitting area on Plane 270°		0.048000 m2	
Emitting area on Plane 90°		0.048000 m2		Glare area at 76°		0.339689 m2	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		05-04-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1006.00 lm	
LED Flux=1456,36lm LED Power=17W Eff=69% EfcLed=86lm/W EfcLum=59lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	21 46 73 50 100			D DIN 5040	C11		
F UTE	0.50 J + 0.50 T			B NBN	BZ 9		

360mm x 50mm




Semipiani C

180.0 ——— 0.0  
270.0 - - - - - 90.0

ULOR 50.00 %

DLOR 50.00 %

RN 50.00 %



## Luminaire

Code 1212t00A  
Name Alphabet of light - t + support

## Measur.

Code FTS1700498  
Name Alphabet of light - t + support

Luminaire Flux	1006.00 lm	Luminaire Power	17.00 W	Efficacy	59.18 lm/W	Efficiency	100.00%
Lamps Flux	1006.00 lm	Maximum value	138.19 cd/klm	Position	C=180.00 G=90.00	CG Sym. on planes 0-180	
Rectangular Luminaire		Length	360 mm	Width	50 mm	Height	960 mm
Rectangular Luminous Area		Length	360 mm	Width	50 mm	Height	960 mm
Horizontal Luminous Area		0.018000 m2		Emitting area on Plane 180°		0.345600 m2	
Emitting area on Plane 0°		0.345600 m2		Emitting area on Plane 270°		0.048000 m2	
Emitting area on Plane 90°		0.048000 m2		Glare area at 76°		0.339689 m2	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		05-04-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1006.00 lm	
LED Flux=1456,36lm LED Power=17W Eff=69% EfcLed=86lm/W EfcLum=59lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	21 46 73 50 100			D DIN 5040	C11		
F UTE	0.50 J + 0.50 T			B NBN	BZ 9		

Apertura a sinistra non trovata, gamma =-90

Apertura a sinistra non trovata, gamma =-90

Apertura a sinistra non trovata, gamma =-90