

## Luminaire


Code 1211X00A  
Name Alphabet of light - X + support

## Measurem.

Code FTS1700528  
Name Alphabet of light - X + support

Luminaire Flux	1721.00 lm	Luminaire Power	27.00 W	Efficacy	63.74 lm/W	Efficiency	100.00%
Lamps Flux	1721.00 lm	Maximum value	138.19 cd/klm	Position	C=180.00 G=90.00	CG Sym. on planes 0-180	
Rectangular Luminaire		Length	900 mm	Width	50 mm	Height	960 mm
Rectangular Luminous Area		Length	900 mm	Width	50 mm	Height	959 mm
Horizontal Luminous Area		0.045000 m2		Emitting area on Plane 180°		0.864000 m2	
Emitting area on Plane 0°		0.864000 m2		Emitting area on Plane 270°		0.048000 m2	
Emitting area on Plane 90°		0.048000 m2		Glare area at 76°		0.849222 m2	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		05-04-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1721.00 lm	
LED Flux=2496,96lm LED Power=27W Eff=69% EfcLed=92lm/W EfcLum=64lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	21 46 73 50 100			D DIN 5040	C11		
F UTE	0.50 J + 0.50 T			B NBN	BZ 9		

900mm x 50mm




Semipiani C

180.0 ——— 0.0  
270.0 - - - - - 90.0

ULOR 50.00 %

DLOR 50.00 %

RN 50.00 %



## Luminaire

Code 1211X00A  
Name Alphabet of light - X + support

## Measur.

Code FTS1700528  
Name Alphabet of light - X + support

Luminaire Flux	1721.00 lm	Luminaire Power	27.00 W	Efficacy	63.74 lm/W	Efficiency	100.00%
Lamps Flux	1721.00 lm	Maximum value	138.19 cd/klm	Position	C=180.00 G=90.00	CG Sym. on planes 0-180	
Rectangular Luminaire		Length	900 mm	Width	50 mm	Height	960 mm
Rectangular Luminous Area		Length	900 mm	Width	50 mm	Height	959 mm
Horizontal Luminous Area		0.045000 m2		Emitting area on Plane 180°		0.864000 m2	
Emitting area on Plane 0°		0.864000 m2		Emitting area on Plane 270°		0.048000 m2	
Emitting area on Plane 90°		0.048000 m2		Glare area at 76°		0.849222 m2	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		05-04-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1721.00 lm	
LED Flux=2496,96lm LED Power=27W Eff=69% EfcLed=92lm/W EfcLum=64lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	21 46 73 50 100			D DIN 5040	C11		
F UTE	0.50 J + 0.50 T			B NBN	BZ 9		

Apertura a sinistra non trovata, gamma =-90

Apertura a sinistra non trovata, gamma =-90

Apertura a sinistra non trovata, gamma =-90