

Luminaire

Code 1210600A
Name Alphabet of light - 6 + support

Measurem.

Code FTS1700537
Name Alphabet of light - 6 + support

| | | | | | | | |
|--|-----------------|-----------------|---------------|-----------------------------|------------------|-------------------------|---------|
| Luminaire Flux | 1656.00 lm | Luminaire Power | 25.00 W | Efficacy | 66.24 lm/W | Efficiency | 100.00% |
| Lamps Flux | 1656.00 lm | Maximum value | 138.19 cd/klm | Position | C=180.00 G=90.00 | CG Sym. on planes 0-180 | |
| Rectangular Luminaire | | Length | 660 mm | Width | 50 mm | Height | 960 mm |
| Rectangular Luminous Area | | Length | 660 mm | Width | 50 mm | Height | 959 mm |
| Horizontal Luminous Area | | 0.033000 m2 | | Emitting area on Plane 180° | | 0.633600 m2 | |
| Emitting area on Plane 0° | | 0.633600 m2 | | Emitting area on Plane 270° | | 0.048000 m2 | |
| Emitting area on Plane 90° | | 0.048000 m2 | | Glare area at 76° | | 0.622763 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Sym. on planes 0-180 | |
| Date | | 05-04-2017 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 1656.00 lm | |
| LED Flux=2392,12lm LED Power=25W Eff=69% EfcLed=96lm/W EfcLum=66lm/W Ra=80 SDCM=3 L70(6K)=50000h | | | | | | | |
| C.I.E. | 21 46 73 50 100 | | | D DIN 5040 | C11 | | |
| F UTE | 0.50 J + 0.50 T | | | B NBN | BZ 9 | | |

660mm x 50mm




Semipiani C

180.0 ——— 0.0
270.0 - - - - - 90.0

ULOR 50.00 %

DLOR 50.00 %

RN 50.00 %



Luminaire

Code 1210600A
Name Alphabet of light - 6 + support

Measurem.

Code FTS1700537
Name Alphabet of light - 6 + support

| | | | | | | | |
|--|-----------------|-----------------|---------------|-----------------------------|------------------|-------------------------|---------|
| Luminaire Flux | 1656.00 lm | Luminaire Power | 25.00 W | Efficacy | 66.24 lm/W | Efficiency | 100.00% |
| Lamps Flux | 1656.00 lm | Maximum value | 138.19 cd/klm | Position | C=180.00 G=90.00 | CG Sym. on planes 0-180 | |
| Rectangular Luminaire | | Length | 660 mm | Width | 50 mm | Height | 960 mm |
| Rectangular Luminous Area | | Length | 660 mm | Width | 50 mm | Height | 959 mm |
| Horizontal Luminous Area | | 0.033000 m2 | | Emitting area on Plane 180° | | 0.633600 m2 | |
| Emitting area on Plane 0° | | 0.633600 m2 | | Emitting area on Plane 270° | | 0.048000 m2 | |
| Emitting area on Plane 90° | | 0.048000 m2 | | Glare area at 76° | | 0.622763 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Sym. on planes 0-180 | |
| Date | | 05-04-2017 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 1656.00 lm | |
| LED Flux=2392,12lm LED Power=25W Eff=69% EfcLed=96lm/W EfcLum=66lm/W Ra=80 SDCM=3 L70(6K)=50000h | | | | | | | |
| C.I.E. | 21 46 73 50 100 | | | D DIN 5040 | C11 | | |
| F UTE | 0.50 J + 0.50 T | | | B NBN | BZ 9 | | |

Apertura a sinistra non trovata, gamma =-90

Apertura a sinistra non trovata, gamma =-90

Apertura a sinistra non trovata, gamma =-90