

Luminaire

Code 1212p00A
Name Alphabet of light - p + support

Measurem.

Code FTS1700494
Name Alphabet of light - p + support

Luminaire Flux	1511.00 lm	Luminaire Power	23.00 W	Efficacy	65.70 lm/W	Efficiency	100.00%
Lamps Flux	1511.00 lm	Maximum value	138.19 cd/klm	Position	C=180.00 G=90.00	CG Sym. on planes 0-180	
Rectangular Luminaire		Length	660 mm	Width	50 mm	Height	990 mm
Rectangular Luminous Area		Length	660 mm	Width	50 mm	Height	989 mm
Horizontal Luminous Area		0.033000 m2		Emitting area on Plane 180°		0.653400 m2	
Emitting area on Plane 0°		0.653400 m2		Emitting area on Plane 270°		0.049500 m2	
Emitting area on Plane 90°		0.049500 m2		Glare area at 76°		0.641975 m2	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		05-04-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1511.00 lm	
LED Flux=2184,24lm LED Power=23W Eff=69% EfcLed=95lm/W EfcLum=66lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	21 46 73 50 100			D DIN 5040	C11		
F UTE	0.50 J + 0.50 T			B NBN	BZ 9		


660mm x 50mm



Semipiani C

180.0 ——— 0.0
270.0 - - - - 90.0

ULOR 50.00 %
DLOR 50.00 %
RN 50.00 %



Luminaire

Code 1212p00A
Name Alphabet of light - p + support

Measur.

Code FTS1700494
Name Alphabet of light - p + support

Luminaire Flux	1511.00 lm	Luminaire Power	23.00 W	Efficacy	65.70 lm/W	Efficiency	100.00%
Lamps Flux	1511.00 lm	Maximum value	138.19 cd/klm	Position	C=180.00 G=90.00	CG Sym. on planes 0-180	
Rectangular Luminaire		Length	660 mm	Width	50 mm	Height	990 mm
Rectangular Luminous Area		Length	660 mm	Width	50 mm	Height	989 mm
Horizontal Luminous Area		0.033000 m2		Emitting area on Plane 180°		0.653400 m2	
Emitting area on Plane 0°		0.653400 m2		Emitting area on Plane 270°		0.049500 m2	
Emitting area on Plane 90°		0.049500 m2		Glare area at 76°		0.641975 m2	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		05-04-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1511.00 lm	
LED Flux=2184,24lm LED Power=23W Eff=69% EfcLed=95lm/W EfcLum=66lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	21 46 73 50 100			D DIN 5040	C11		
F UTE	0.50 J + 0.50 T			B NBN	BZ 9		

Apertura a sinistra non trovata, gamma =-90

Apertura a sinistra non trovata, gamma =-90

Apertura a sinistra non trovata, gamma =-90