




Attention: Read and understand these instructions before installing fixture. This fixture is intended for installation in accordance with National Electric Code and local regulation: To assure full compliance with local codes and regulations, check with your local electrical inspector before installation. This equipment is guaranteed only when used as indicated in these instructions; therefore they should be kept for future reference. To prevent electrical shock, turn off power supply before carrying out any connection or maintenance operations.


Make sure you have all the elements of the fixture. Your box should contain the following parts:



STEP 1

1.1 Mark the ceiling cutout location and size using the dimensions below.


1.1




STEP 1

1.1 Loosen the 2 screws holding the housing cover and remove it.
1.2 Pry off the electrical knock-out where the electrical wiring will come through.

1.1



1.2






STEP 3

- 3.1 Insert the electrical wiring through the housing and fix in place.
- 3.2 Make the electrical connections using the diagram below.
- 3.3 Close up the housing with the previously removed cover and tighten both Philips screws.

3.1



3.2


MAINS WIRING:

CEILING WIRES		HOUSING WIRES
GREEN	(G)	GREEN/YELLOW
BLACK	(L)	BLACK
WHITE	(N)	WHITE


0-10V DIMMING WIRES:

CEILING WIRES		HOUSING WIRES
0-10V (+)	(+)	VIOLET (+)
0-10V (-)	(-)	GREY (-)

DIMMING WIRES OPTIONAL
IF NOT USING, DO NOT CAP TOGETHER
AS IT WILL DIM THE FIXTURE TO MINIMUM



3.3







STEP 4

- 4.1 Insert the housing through the hole, fixing the box to a structure if required.
4.2


4.1





STEP 5

- 5.1 Remove the 2 screws using the supplied Hex key to open up the connection box.
5.2 Loosen the bracket screws to remove sliding brackets, and insert connection box into the ceiling.
5.3 Re-insert the 2 sliding brackets, and lock them in place using the screws.


5.1



5.2



5.3







STEP 5 (cont.)

Depending on the layout, you will have different cables going to the fixture. These will need to be wired to their respective LED driver inside the driver housing. Polarity must be respected to prevent damage.
5.4 Make the appropriate connections as shown below.


4 Wire / 1 Connector





8 Wire / 2 Connector




4 Wire / 2 Connector



8 Wire / 4 Connector



5.4





STEP 6

6.1 Insert the Feed Cable through the connection box cover, and mount the cover using the screws removed in Step 5.1

