

Luminaire

Code 2061118A 25W
Name RIPPLE 70 SOSPENSIONE P/CUT

Measur.

Code FTS2000799
Name RIPPLE 70 SOSPENSIONE P/CUT

Luminaire Flux	2104.85 lm	Luminaire Power	25.00 W	Efficacy	84.19 lm/W	Efficiency	100.00%
Sources Flux	2104.85 lm	Maximum value	353.30 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	700 mm	Height	30 mm		
Round Luminous Area		Diam.	650 mm	Height	0 mm		
Horizontal Luminous Area			0.331831 m ²	Emitting area on Plane 180°			0.000000 m ²
Emitting area on Plane 0°			0.000000 m ²	Emitting area on Plane 270°			0.000000 m ²
Emitting area on Plane 90°			0.000000 m ²	Glare area at 76°			0.080277 m ²
Coordinate system		CG		Symmetry Type			Rotosymmetrical
Date		09-09-2021		Maximum Gamma Angle			180
Measurement Distance		0.00		Measurement Flux			2104.85 lm


LED Flux=4147lm LED Power=21W Eff=51% EfcLed=197lm/W EfcLum=84lm/W CCT=3000K Ra=90 SDCM=2 L70(6K)=50000h

C.I.E. 47 79 96 100 100
F UTE 1.00 E

D DIN 5040
B NBN

A30
BZ 5 / 1.25 / BZ 4

Diam=700mm




C Halfplanes

180.0 — 0.0

ULOR 0.01 %

DLOR 99.99 %

RN 0.01 %



Luminaire

Code 2061018A 25W
Name RIPPLE 70 SOSPENSIONE P/CUT

Measurem.


Code FTS2000799
Name RIPPLE 70 SOSPENSIONE P/CUT

Luminaire Flux	2104.85 lm	Luminaire Power	25.00 W	Efficacy	84.19 lm/W	Efficiency	100.00%
Sources Flux	2104.85 lm	Maximum value	353.30 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.48	2.96	4.44	5.91	7.39	OC	1.48	2.96	4.44	5.91	7.39
OB	1.48	2.96	4.44	5.91	7.39	OD	1.48	2.96	4.44	5.91	7.39

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	743.63	739.98	711.00	657.43	582.44	489.67	382.24	264.00	139.69	31.58
OB	743.63	739.98	711.00	657.43	582.44	489.67	382.24	264.00	139.69	31.58
OC	743.63	739.98	711.00	657.43	582.44	489.67	382.24	264.00	139.69	31.58
OD	743.63	739.98	711.00	657.43	582.44	489.67	382.24	264.00	139.69	31.58



H[m]	D[m]	Max lux	Med lux	Alpha=55.9°+55.9°	G=0.0
1.00	2.96	744	182		
2.00	5.91	186	45		
3.00	8.87	83	20		
4.00	11.83	46	11		
5.00	14.79	30	7		