

Luminaire


Code 1215T00A
Name AOL MINI W T UPPERCASE

Measurerm.

Code FTS2400026
Name AOL MINI W T UPPERCASE

Luminaire Flux	616 lm	Luminaire Power	6.0 W	Efficacy	102.667 lm/W	Efficiency	100.00%
Source Flux	616 lm	Maximum value	186.85 cd/klm	Position	C=70.00 G=2.00	CG	Asymmetrical
Rectangular Luminaire		Length	355 mm	Width	245 mm	Height	42 mm
Rectangular Luminous Area		Length	355 mm	Width	41 mm	Height	25 mm
Horizontal Luminous Area		0.014555 m ²		Emitting area on Plane 180°		0.008875 m ²	
Emitting area on Plane 0°		0.008875 m ²		Emitting area on Plane 270°		0.001025 m ²	
Emitting area on Plane 90°		0.001025 m ²		Glare area at 76°		0.012133 m ²	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		19-12-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		616 lm	
LED Flux=778lm LED Power=6W Eff=79% EfcLed=130lm/W EfcLum=103lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	36 65 86 72 100			D DIN 5040	B21		
F UTE	0.72 H + 0.28 T			B NBN	BZ 6		

355mm x 245mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 27.80 %
DLOR 72.20 %
RN 27.80 %

