

Luminaire

Code M259120

Name EVERYTHING 105 QUADRATO TRIM FISSO LED 4000K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO


Measurement

Code FTS1602395

Name EVERYTHING 105 QUADRATO TRIM FISSO LED 4000K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO

Luminaire Flux	726.02 lm	Luminaire Power	13.00 W	Efficacy	55.85 lm/W	Efficiency	100.00%
Lamps Flux	726.02 lm	Maximum value	1723.54 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area		Length Diam.	105 mm 50 mm	Width Height	105 mm 0 mm	Height	115 mm
Horizontal Luminous Area		0.001963 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000475 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		06-07-2015		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		726.02 lm	
LED Flux=1432lm LED Power=13W Eff=50,7% EfcLed=110lm/W EfcLum=56lm/W Ra=90 SDCM=3 L70(6K)=50000- L70							
C.I.E.	95 100 100 100 100			D DIN 5040		A60	
F UTE	1.00 A			B NBN		BZ 1	

105mm x 105mm




Semipiani C

180.0 — 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code M259120

Name EVERYTHING 105 QUADRATO TRIM FISSO LED 4000K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO

Measurement

Code FTS1602395


Name EVERYTHING 105 QUADRATO TRIM FISSO LED 4000K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO

Luminaire Flux	726.02 lm	Luminaire Power	13.00 W	Efficacy	55.85 lm/W	Efficiency	100.00%
Lamps Flux	726.02 lm	Maximum value	1723.54 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area		Length Diam.	105 mm 50 mm	Width Height	105 mm 0 mm	Height	115 mm
Horizontal Luminous Area		0.001963 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000475 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		06-07-2015		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		726.02 lm	
LED Flux=1432lm LED Power=13W Eff=50,7% EfcLed=110lm/W EfcLum=56lm/W Ra=90 SDCM=3 L70(6K)=50000- L70							
C.I.E. F UTE	95 100 100 100 100 1.00 A			D DIN 5040 B NBN	A60 BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.38	0.76	1.14	1.51	1.89	OC	0.38	0.76	1.14	1.51	1.89
OB	0.38	0.76	1.14	1.51	1.89	OD	0.38	0.76	1.14	1.51	1.89

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1251.32	1179.11	834.99	482.28	195.65	48.22	2.61	0.54	0.36	0.27
OB	1251.32	1179.11	834.99	482.28	195.65	48.22	2.61	0.54	0.36	0.27
OC	1251.32	1179.11	834.99	482.28	195.65	48.22	2.61	0.54	0.36	0.27
OD	1251.32	1179.11	834.99	482.28	195.65	48.22	2.61	0.54	0.36	0.27



H[m]	D[m]	Max lux	Med lux	Alpha=20.7°+20.7°	G=0.0
1.00	0.76	1251	707		
2.00	1.51	313	177		
3.00	2.27	139	79		
4.00	3.03	78	44		
5.00	3.79	50	28		

Luminaire

Code M259120

Name EVERYTHING 105 QUADRATO TRIM FISSO LED 4000K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO

Measur.

Code FTS1602395

Name EVERYTHING 105 QUADRATO TRIM FISSO LED 4000K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO

Luminaire Flux	726.02 lm	Luminaire Power	13.00 W	Efficacy	55.85 lm/W	Efficiency	100.00%
Lamps Flux	726.02 lm	Maximum value	1723.54 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	19.5	20.1	19.7	20.3	20.5	19.5	20.1	19.7	20.3	20.5
x=2H y=3H	19.3	19.9	19.6	20.2	20.4	19.3	19.9	19.6	20.2	20.4
x=2H y=4H	19.3	19.8	19.6	20.1	20.4	19.3	19.8	19.6	20.1	20.4
x=2H y=6H	19.2	19.7	19.5	20.0	20.3	19.2	19.7	19.5	20.0	20.3
x=2H y=8H	19.2	19.7	19.5	20.0	20.3	19.2	19.7	19.5	20.0	20.3
x=2H y=12H	19.1	19.6	19.5	19.9	20.2	19.1	19.6	19.5	19.9	20.2
x=4H y=2H	19.3	19.8	19.6	20.1	20.4	19.3	19.8	19.6	20.1	20.4
x=4H y=3H	19.1	19.6	19.5	19.9	20.2	19.1	19.6	19.5	19.9	20.2
x=4H y=4H	19.0	19.5	19.4	19.8	20.1	19.0	19.5	19.4	19.8	20.1
x=4H y=6H	19.0	19.3	19.4	19.7	20.0	19.0	19.3	19.4	19.7	20.0
x=4H y=8H	18.9	19.2	19.3	19.6	20.0	18.9	19.2	19.3	19.6	20.0
x=4H y=12H	18.9	19.2	19.3	19.6	20.0	18.9	19.2	19.3	19.6	20.0
x=8H y=4H	18.9	19.2	19.3	19.6	20.0	18.9	19.2	19.3	19.6	20.0
x=8H y=6H	18.8	19.1	19.3	19.5	20.0	18.8	19.1	19.3	19.5	20.0
x=8H y=8H	18.8	19.0	19.3	19.4	19.9	18.8	19.0	19.3	19.4	19.9
x=8H y=12H	18.8	18.9	19.2	19.4	19.9	18.8	18.9	19.2	19.4	19.9
x=12H y=4H	18.9	19.1	19.3	19.5	20.0	18.9	19.1	19.3	19.5	20.0
x=12H y=6H	18.8	19.0	19.3	19.4	19.9	18.8	19.0	19.3	19.4	19.9
x=12H y=8H	18.8	18.9	19.2	19.4	19.9	18.8	18.9	19.2	19.4	19.9