

Luminaire

Code M278820

Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO


Measurem.

Code FTS1602119

Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO

Luminaire Flux	982.73 lm	Luminaire Power	13.00 W	Efficacy	75.59 lm/W	Efficiency	100.00%
Lamps Flux	982.73 lm	Maximum value	3539.08 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	80 mm	Height	115 mm		
Round Luminous Area		Diam.	50 mm	Height	0 mm		
Horizontal Luminous Area		0.001963 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000475 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		26-06-2015		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		982.73 lm	
LED Flux=1390lm LED Power=13W Eff=70,7% EfcLed=107lm/W EfcLum=76lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	96 100 100 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Diam=80mm




Semipiani C

180.0 — 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code M278820

Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO

Measurement

Code FTS1602119


Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO

Luminaire Flux	982.73 lm	Luminaire Power	13.00 W	Efficacy	75.59 lm/W	Efficiency	100.00%
Lamps Flux	982.73 lm	Maximum value	3539.08 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	80 mm 50 mm	Height Height	115 mm 0 mm		
Horizontal Luminous Area		0.001963 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000475 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		26-06-2015		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		982.73 lm	
LED Flux=1390lm LED Power=13W Eff=70,7% EfcLed=107lm/W EfcLum=76lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	96 100 100 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.21	0.43	0.64	0.86	1.07	OC	0.21	0.43	0.64	0.86	1.07
OB	0.21	0.43	0.64	0.86	1.07	OD	0.21	0.43	0.64	0.86	1.07

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	3477.96	3023.54	1323.08	463.53	138.38	44.06	15.03	0.49	0.32	0.28
OB	3477.96	3023.54	1323.08	463.53	138.38	44.06	15.03	0.49	0.32	0.28
OC	3477.96	3023.54	1323.08	463.53	138.38	44.06	15.03	0.49	0.32	0.28
OD	3477.96	3023.54	1323.08	463.53	138.38	44.06	15.03	0.49	0.32	0.28



H[m]	D[m]	Max lux	Med lux	Alpha=12.1°+12.1°	G=0.0
1.00	0.43	3478	2141		
2.00	0.86	869	535		
3.00	1.29	386	238		
4.00	1.72	217	134		
5.00	2.15	139	86		

Luminaire

Code M278820

Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO

Measur.

Code FTS1602119

Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K FLOOD CORNICE BIANCO / DEFL. METALLIZZATO

Luminaire Flux	982.73 lm	Luminaire Power	13.00 W	Efficacy	75.59 lm/W	Efficiency	100.00%
Lamps Flux	982.73 lm	Maximum value	3539.08 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	17.1	17.8	17.4	18.0	18.2	17.1	17.8	17.4	18.0	18.2
x=2H y=3H	17.0	17.6	17.3	17.9	18.1	17.0	17.6	17.3	17.9	18.1
x=2H y=4H	16.9	17.5	17.2	17.8	18.0	16.9	17.5	17.2	17.8	18.0
x=2H y=6H	16.9	17.4	17.2	17.7	18.0	16.9	17.4	17.2	17.7	18.0
x=2H y=8H	16.8	17.3	17.2	17.6	17.9	16.8	17.3	17.2	17.6	17.9
x=2H y=12H	16.8	17.3	17.2	17.6	17.9	16.8	17.3	17.2	17.6	17.9
x=4H y=2H	17.0	17.6	17.3	17.8	18.1	17.0	17.6	17.3	17.8	18.1
x=4H y=3H	16.9	17.3	17.2	17.6	17.9	16.9	17.3	17.2	17.6	17.9
x=4H y=4H	16.8	17.2	17.1	17.5	17.9	16.8	17.2	17.1	17.5	17.9
x=4H y=6H	16.7	17.0	17.1	17.4	17.8	16.7	17.0	17.1	17.4	17.8
x=4H y=8H	16.7	17.0	17.1	17.4	17.8	16.7	17.0	17.1	17.4	17.8
x=4H y=12H	16.6	16.9	17.1	17.3	17.7	16.6	16.9	17.1	17.3	17.7
x=8H y=4H	16.7	17.0	17.1	17.3	17.7	16.7	17.0	17.1	17.3	17.7
x=8H y=6H	16.6	16.8	17.0	17.2	17.7	16.6	16.8	17.0	17.2	17.7
x=8H y=8H	16.5	16.7	17.0	17.2	17.6	16.5	16.7	17.0	17.2	17.6
x=8H y=12H	16.5	16.7	17.0	17.1	17.6	16.5	16.7	17.0	17.1	17.6
x=12H y=4H	16.6	16.9	17.1	17.3	17.7	16.6	16.9	17.1	17.3	17.7
x=12H y=6H	16.5	16.7	17.0	17.2	17.6	16.5	16.7	17.0	17.2	17.6
x=12H y=8H	16.5	16.6	17.0	17.1	17.6	16.5	16.6	17.0	17.1	17.6