

## Luminaire

Code M273720

Name EVERYTHING 80 QUADRATO TRIM FISSO LED 4000K SPOT CORNICE BIANCO / DEFL. METALLIZZATO


## Measurem.

Code FTS1602209

Name EVERYTHING 80 QUADRATO TRIM FISSO LED 4000K SPOT CORNICE BIANCO / DEFL. METALLIZZATO

Luminaire Flux	1118.39 lm	Luminaire Power	13.00 W	Efficacy	86.03 lm/W	Efficiency	100.00%
Lamps Flux	1118.39 lm	Maximum value	3651.00 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area	Length Diam.	80 mm 50 mm	Width Height	80 mm 0 mm	Height	115 mm	
Horizontal Luminous Area	0.001963 m2		Emitting area on Plane 180°	0.000000 m2			
Emitting area on Plane 0°	0.000000 m2		Emitting area on Plane 270°	0.000000 m2			
Emitting area on Plane 90°	0.000000 m2		Glare area at 76°	0.000475 m2			
Coordinate system	CG		Symmetry Type	Rotosymmetrical			
Date	08-04-2015		Maximum Gamma Angle	90			
Measurement Distance	0.00		Measurement Flux	1118.39 lm			
LED Flux=1432lm LED Power=13W Eff=78,1% EfcLed=110lm/W EfcLum=86lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1


80mm x 80mm



Semipiani C

180.0 — 0.0

ULOR 0.00 %  
DLOR100.00 %  
RN 0.00 %



## Luminaire

Code M273720

Name EVERYTHING 80 QUADRATO TRIM FISSO LED 4000K SPOT CORNICE BIANCO / DEFL. METALLIZZATO

## Measurement

Code FTS1602209


Name EVERYTHING 80 QUADRATO TRIM FISSO LED 4000K SPOT CORNICE BIANCO / DEFL. METALLIZZATO

Luminaire Flux	1118.39 lm	Luminaire Power	13.00 W	Efficacy	86.03 lm/W	Efficiency	100.00%
Lamps Flux	1118.39 lm	Maximum value	3651.00 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area		Length Diam.	80 mm 50 mm	Width Height	80 mm 0 mm	Height	115 mm
Horizontal Luminous Area		0.001963 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000475 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		08-04-2015		Maximum Gamma Angle		90	
Measurement Distance		0.00		Measurement Flux		1118.39 lm	
LED Flux=1432lm LED Power=13W Eff=78,1% EfcLed=110lm/W EfcLum=86lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E. F UTE	99	100	100	100	100	D DIN 5040 B NBN	A60 BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.22	0.44	0.65	0.87	1.09	OC	0.22	0.44	0.65	0.87	1.09
OB	0.22	0.44	0.65	0.87	1.09	OD	0.22	0.44	0.65	0.87	1.09

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	4083.25	3547.79	1563.83	567.65	151.36	26.45	0.46	0.00	0.00	0.00
OB	4083.25	3547.79	1563.83	567.65	151.36	26.45	0.46	0.00	0.00	0.00
OC	4083.25	3547.79	1563.83	567.65	151.36	26.45	0.46	0.00	0.00	0.00
OD	4083.25	3547.79	1563.83	567.65	151.36	26.45	0.46	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=12.3°+12.3°	G=0.0
1.00	0.44	4083	2510		
2.00	0.87	1021	627		
3.00	1.31	454	279		
4.00	1.74	255	157		
5.00	2.18	163	100		

## Luminaire

Code M273720

Name EVERYTHING 80 QUADRATO TRIM FISSO LED 4000K SPOT CORNICE BIANCO / DEFL. METALLIZZATO

## Measur.

Code FTS1602209

Name EVERYTHING 80 QUADRATO TRIM FISSO LED 4000K SPOT CORNICE BIANCO / DEFL. METALLIZZATO

Luminaire Flux	1118.39 lm	Luminaire Power	13.00 W	Efficacy	86.03 lm/W	Efficiency	100.00%
Lamps Flux	1118.39 lm	Maximum value	3651.00 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

UGR  
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	16.0	16.7	16.3	16.9	17.1	16.0	16.7	16.3	16.9	17.1
x=2H y=3H	15.9	16.5	16.2	16.7	16.9	15.9	16.5	16.2	16.7	16.9
x=2H y=4H	15.8	16.4	16.1	16.6	16.9	15.8	16.4	16.1	16.6	16.9
x=2H y=6H	15.8	16.3	16.1	16.5	16.8	15.8	16.3	16.1	16.5	16.8
x=2H y=8H	15.7	16.2	16.0	16.5	16.8	15.7	16.2	16.0	16.5	16.8
x=2H y=12H	15.7	16.1	16.0	16.4	16.8	15.7	16.1	16.0	16.4	16.8
x=4H y=2H	15.8	16.4	16.1	16.6	16.9	15.8	16.4	16.1	16.6	16.9
x=4H y=3H	15.7	16.1	16.0	16.4	16.8	15.7	16.1	16.0	16.4	16.8
x=4H y=4H	15.6	16.0	16.0	16.3	16.7	15.6	16.0	16.0	16.3	16.7
x=4H y=6H	15.5	15.9	15.9	16.2	16.6	15.5	15.9	15.9	16.2	16.6
x=4H y=8H	15.5	15.8	15.9	16.2	16.5	15.5	15.8	15.9	16.2	16.5
x=4H y=12H	15.4	15.7	15.9	16.1	16.5	15.4	15.7	15.9	16.1	16.5
x=8H y=4H	15.5	15.8	15.9	16.2	16.5	15.5	15.8	15.9	16.2	16.5
x=8H y=6H	15.4	15.6	15.8	16.0	16.5	15.4	15.6	15.8	16.0	16.5
x=8H y=8H	15.4	15.5	15.8	16.0	16.4	15.4	15.5	15.8	16.0	16.4
x=8H y=12H	15.3	15.4	15.8	15.9	16.4	15.3	15.4	15.8	15.9	16.4
x=12H y=4H	15.4	15.7	15.9	16.1	16.5	15.4	15.7	15.9	16.1	16.5
x=12H y=6H	15.4	15.5	15.8	16.0	16.4	15.4	15.5	15.8	16.0	16.4
x=12H y=8H	15.3	15.4	15.8	15.9	16.4	15.3	15.4	15.8	15.9	16.4