

## Luminaire

Code M2883W01+M197400

Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 3000K DIMMERABILE 1184MM + INDIRETTA LED+ OTTICA DIFFONDENTE PER LED


## Measurem.

Code FTS1601413

Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 3000K DIMMERABILE 1184MM + INDIRETTA LED+ OTTICA DIFFONDENTE PER LED

Luminaire Flux	4436.10 lm	Luminaire Power	62.00 W	Efficacy	71.55 lm/W	Efficiency	100.00%
Lamps Flux	4436.10 lm	Maximum value	243.09 cd/klm	Position	C=0.00 G=180.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1185 mm	Width	45 mm	Height	110 mm
Rectangular Luminous Area		Length	1185 mm	Width	32 mm	Height	0 mm
Horizontal Luminous Area		0.037920 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.009174 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		23-06-2016		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4436.10 lm	
LED Flux=7571,94lm LED Power=48W Eff=59% EfcLed=158lm/W EfcLum=72lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	49 80 96 44 100			D DIN 5040		C32	
F UTE	0.44 E + 0.56 T			B NBN		BZ 4	

1185mm x 45mm




Semipiani C

180.0 ——— 0.0  
270.0 - - - - 90.0

ULOR 55.76 %

DLOR 44.24 %

RN 55.76 %



## Luminaire

Code M2883W01+M197400

Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 3000K DIMMERABILE 1184MM + INDIRETTA LED+ OTTICA DIFFONDENTE PER LED

## Measurement

Code FTS1601413


Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 3000K DIMMERABILE 1184MM + INDIRETTA LED+ OTTICA DIFFONDENTE PER LED

Luminaire Flux	4436.10 lm	Luminaire Power	62.00 W	Efficacy	71.55 lm/W	Efficiency	100.00%
Lamps Flux	4436.10 lm	Maximum value	243.09 cd/klm	Position	C=0.00 G=180.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1185 mm	Width	45 mm	Height	110 mm
Rectangular Luminous Area		Length	1185 mm	Width	32 mm	Height	0 mm
Horizontal Luminous Area		0.037920 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.009174 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		23-06-2016		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4436.10 lm	
LED Flux=7571,94lm LED Power=48W Eff=59% EfcLed=158lm/W EfcLum=72lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	49 80 96 44 100			D DIN 5040	C32		
F UTE	0.44 E + 0.56 T			B NBN	BZ 4		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.04	2.08	3.12	4.16	5.21	OC	1.06	2.13	3.19	4.25	5.32
OB	1.04	2.08	3.12	4.16	5.21	OD	1.06	2.13	3.19	4.25	5.32

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1078.39	1070.71	1017.35	908.46	746.78	561.60	382.82	234.49	123.35	47.87
OB	1078.39	1070.71	1017.35	908.46	746.78	561.60	382.82	234.49	123.35	47.87
OC	1078.39	1071.16	1018.11	912.12	754.93	573.07	392.74	241.07	125.40	46.60
OD	1078.39	1071.16	1018.11	912.12	754.93	573.07	392.74	241.07	125.40	46.60



5.00	10.41	43	15		
4.00	8.33	67	24		
3.00	6.25	120	42		
2.00	4.16	270	94		
1.00	2.08	1078	377		
H[m]	D[m]	Max lux	Med lux	Alpha=46.2°+46.2°	G=0.0

5.00	10.63	43	15		
4.00	8.50	67	24		
3.00	6.38	120	42		
2.00	4.25	270	94		
1.00	2.13	1078	377		
H[m]	D[m]	Max lux	Med lux	Beta=46.8°+46.8°	G=0.0

## Luminaire

Code M2883W01+M197400

Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 3000K DIMMERABILE 1184MM + INDIRETTA LED+ OTTICA DIFFONDENTE PER LED

## Measur.

Code FTS1601413

Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 3000K DIMMERABILE 1184MM + INDIRETTA LED+ OTTICA DIFFONDENTE PER LED

Luminaire Flux	4436.10 lm	Luminaire Power	62.00 W	Efficacy	71.55 lm/W	Efficiency	100.00%
Lamps Flux	4436.10 lm	Maximum value	243.09 cd/klm	Position	C=0.00 G=180.00	CG	Double Symmetrical

UGR  
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions										
ViewedCrosswise	ViewedEndwise					ViewedEndwise				
	17.9	18.6	18.8	19.6	21.1	18.2	18.9	19.1	19.9	21.1
x=2H y=2H	17.9	18.6	18.8	19.6	21.1	18.2	18.9	19.1	19.9	21.1
x=2H y=3H	19.3	20.0	20.3	20.9	22.5	19.6	20.3	20.6	21.3	22.5
x=2H y=4H	19.8	20.5	20.8	21.4	23.1	20.2	20.8	21.2	21.8	23.1
x=2H y=6H	20.2	20.8	21.2	21.7	23.4	20.6	21.2	21.6	22.1	23.4
x=2H y=8H	20.3	20.8	21.3	21.8	23.5	20.7	21.3	21.7	22.2	23.5
x=2H y=12H	20.3	20.9	21.4	21.9	23.6	20.8	21.3	21.8	22.3	23.6
x=4H y=2H	18.5	19.1	19.5	20.1	21.6	18.7	19.3	19.7	20.3	21.6
x=4H y=3H	20.0	20.6	21.0	21.6	23.2	20.3	20.8	21.3	21.8	23.2
x=4H y=4H	20.7	21.1	21.7	22.1	23.8	21.0	21.4	22.0	22.4	23.8
x=4H y=6H	21.1	21.5	22.2	22.6	24.2	21.5	21.9	22.5	22.9	24.2
x=4H y=8H	21.3	21.6	22.3	22.7	24.4	21.6	22.0	22.7	23.0	24.4
x=4H y=12H	21.3	21.7	22.4	22.7	24.5	21.7	22.0	22.8	23.1	24.5
x=8H y=4H	20.9	21.3	21.9	22.3	23.9	21.2	21.5	22.2	22.6	23.9
x=8H y=6H	21.5	21.8	22.5	22.8	24.5	21.8	22.1	22.8	23.1	24.5
x=8H y=8H	21.7	21.9	22.8	23.0	24.7	22.0	22.2	23.1	23.3	24.7
x=8H y=12H	21.8	22.0	22.9	23.1	24.9	22.1	22.4	23.2	23.4	24.9
x=12H y=4H	20.9	21.2	21.9	22.2	23.9	21.1	21.5	22.2	22.5	23.9
x=12H y=6H	21.5	21.8	22.6	22.8	24.5	21.8	22.0	22.9	23.1	24.5
x=12H y=8H	21.7	22.0	22.8	23.0	24.7	22.0	22.3	23.1	23.3	24.7