

Luminaire

Code TB02122
Name VECTOR 20 TRK12 935 SP TITAN.

Measurem.

Code FTS2102434
Name VECTOR 20 TRK12 935 SP TITAN.

Luminaire Flux	176 lm	Luminaire Power	3.0 W	Efficacy	58.690 lm/W	Efficiency	100.00%
Source Flux	176 lm	Maximum value	11314.21 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	20 mm	Height	50 mm		
Round Luminous Area		Diam.	15 mm	Height	0 mm		
Horizontal Luminous Area		0.000177 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000043 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		09-09-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		176 lm	
LED Flux=208lm LED Power=1.9W Eff=85% EfcLed=110lm/W EfcLum=59lm/W CCT=3500K Ra=90 SDCM=3 L70(6K)=36000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Diam=20mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code TB02122
Name VECTOR 20 TRK12 935 SP TITAN.

Measurem.


Code FTS2102434
Name VECTOR 20 TRK12 935 SP TITAN.

Luminaire Flux	176 lm	Luminaire Power	3.0 W	Efficacy	58.690 lm/W	Efficiency	100.00%
Source Flux	176 lm	Maximum value	11314.21 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	20 mm	Height	50 mm		
Round Luminous Area		Diam.	15 mm	Height	0 mm		
Horizontal Luminous Area		0.000177 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000043 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		09-09-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		176 lm	
LED Flux=208lm LED Power=1.9W Eff=85% EfcLed=110lm/W EfcLum=59lm/W CCT=3500K Ra=90 SDCM=3 L70(6K)=36000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.13	0.27	0.40	0.53	0.67	OC	0.13	0.27	0.40	0.53	0.67
OB	0.13	0.27	0.40	0.53	0.67	OD	0.13	0.27	0.40	0.53	0.67

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1992.09	1529.83	163.30	16.57	5.36	1.50	0.44	0.10	0.00	0.00
OB	1992.09	1529.83	163.30	16.57	5.36	1.50	0.44	0.10	0.00	0.00
OC	1992.09	1529.83	163.30	16.57	5.36	1.50	0.44	0.10	0.00	0.00
OD	1992.09	1529.83	163.30	16.57	5.36	1.50	0.44	0.10	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=7.6°+7.6°	G=0.0
1.00	0.27	1992	1298		
2.00	0.53	498	325		
3.00	0.80	221	144		
4.00	1.07	125	81		
5.00	1.33	80	52		