

Luminaire

Code TB42222
Name VECTOR 40 TRK12 PENDANT 935 FL TITAN.

Measurem.

Code FTS1902900
Name VECTOR 40 TRK12 PENDANT 935 FL TITAN.

Luminaire Flux	675 lm	Luminaire Power	10.0 W	Efficacy	67.470 lm/W	Efficiency	100.00%
Source Flux	675 lm	Maximum value	5684.10 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	40 mm	Height	105 mm		
Round Luminous Area		Diam.	33 mm	Height	0 mm		
Horizontal Luminous Area		0.000855 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000207 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		24-10-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		675 lm	
LED Flux=977.4lm LED Power=8W Eff=69% EfcLed=122lm/W EfcLum=67lm/W CCT=3500K Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Diam=40mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code TB42222
Name VECTOR 40 TRK12 PENDANT 935 FL TITAN.

Measurem.


Code FTS1902900
Name VECTOR 40 TRK12 PENDANT 935 FL TITAN.

Luminaire Flux	675 lm	Luminaire Power	10.0 W	Efficacy	67.470 lm/W	Efficiency	100.00%
Source Flux	675 lm	Maximum value	5684.10 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	40 mm	Height	105 mm		
Round Luminous Area		Diam.	33 mm	Height	0 mm		
Horizontal Luminous Area		0.000855 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000207 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		24-10-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		675 lm	
LED Flux=977.4lm LED Power=8W Eff=69% EfcLed=122lm/W EfcLum=67lm/W CCT=3500K Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.36	0.54	0.72	0.91	OC	0.18	0.36	0.54	0.72	0.91
OB	0.18	0.36	0.54	0.72	0.91	OD	0.18	0.36	0.54	0.72	0.91

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	3835.06	3247.28	963.83	210.33	28.89	5.15	2.09	0.60	0.00	0.00
OB	3835.06	3247.28	963.83	210.33	28.89	5.15	2.09	0.60	0.00	0.00
OC	3835.06	3247.28	963.83	210.33	28.89	5.15	2.09	0.60	0.00	0.00
OD	3835.06	3247.28	963.83	210.33	28.89	5.15	2.09	0.60	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=10.3°+10.3°	G=0.0
1.00	0.36	3835	2424		
2.00	0.72	959	606		
3.00	1.09	426	269		
4.00	1.45	240	151		
5.00	1.81	153	97		